

KLUDI PURE&STYLE
single lever basin mixer 75
DN 15

Finishes:
39 matt black

basin mixer
single lever mixer
1-hole mounted
solid handle, metal
aerator M24 PCA
ceramic cartridge with hot water safety device
flow rate at 3 bar 5 l/min.
flexible hoses G3/8 DVGW approved
rapid installation set
EU taxonomy: max. 6 l/min. -
Substantial Contribution (SC) possible

Technical drawing of the shower head assembly showing dimensions:

- Top view dimensions: 125, 110, 90
- Side view dimensions: 1-30, Ø48, 75, 100, 135
- Angle dimension: 27°
- Total height dimension: 390
- Connection type: G $\frac{3}{8}$

The graph shows the relationship between flow rate Q_v (l/min) and pressure p (bar) for a 100 mm³/min air pump. The y-axis ranges from 0 to 8 l/min with major grid lines every 2 units. The x-axis ranges from 0 to 5 bar with major grid lines every 1 unit. The curve starts at the origin (0,0) and rises steeply, passing through approximately (0.5, 3.5) and (1, 4.5). It then levels off, reaching a plateau of approximately 5 l/min at pressures above 2 bar.

Pressure p (bar)	Flow rate Q_v (l/min)
0	0
0.5	3.5
1.0	4.5
2.0	5.0
3.0	5.0
4.0	5.0
5.0	5.0